

TOUCHLESS SENSORS

PARTNER DEVICES QUALIFIED FOR BRIGHTSIGN PLAYERS

BrightSign partners have developed a wide array of touchless interactive devices that use BrightSign media players to enable user engagement via buttons and sensors that don't require a physical touch. Both existing and new interactive signage presentations can take advantage of these sensors. Each device utilizes existing features of BrightSign players to make the integration seamless. Our wide array of I/O ports allow you to connect any device to our USB, GPIO, Serial and Ethernet ports, and our BrightAuthor and BrightAuthor:connected software includes the tools to support the presentations that use these interactive devices.

Audio Authority®

AirSelect™ Proximity Sensors

- Direct replacement for a 19mm push-button
- Elegant proximity sensing
- Indicator lights provide visual feedback
- Programmable proximity range
- Compact hub provides power and intelligence
- Easy plug-and-play installation



bluefin.

Contactless Sensor Buttons

- Short-Range Motion Sensor, up to 2" from button
- 19mm (0.7 in) Button Form Factor
- Matte black plastic with glossy/semi-transparent sensor window
- GPIO Terminal connection compatible with BrightSign
- Uses the GPIO Input Events in BrightAuthor to trigger state changes and commands

neXmosphere

elements for experience

AirTouch & AirGesture Sensors

- Touch: enables a button-type of interaction by detecting when a hand is close to, but not touching, the sensor
- Gestures: detects left/right/up/down swipes of the hand above the sensor for navigation in signage
- Also synchronizes with LED strip lighting to indicate detections

